

# AMA

## PISANI

A.M.P PISANI S.r.l. Via Ungaretti 6/8 27024 CILAVEGNA (PV) ITALY

Phone +39 0381 96128 Fax +39 0381 969100 [www.amppisani.com](http://www.amppisani.com) email: [info@amppisani.com](mailto:info@amppisani.com)



**P88/6E**

**MOLDING MACHINE FOR BRA CUPS IN FOAM WITH SIX MOLDS**

## **MOLDING MACHINE FOR BRA CUPS IN FOAM WITH SIX MOLDS CLASS P88/6E**

The machine P88/6E is a flexible unit with six DOUBLE molds and pliers specifically developed to mold bra cups in FOAM which produce No. 12 cups for each molding cycle.

### **TECHNICAL FEATURES**

- The machine consists of four molding heads where it is possible to put one male mold in upper position and one female counter mold (fixed) on the lower table. The molds are normally double (two cups on each mold) with maximum dimensions 400 x 280 x H=150 mm.
- The operator positions the rectangular pieces of foam on the lower molds then he starts the molding cycle.
- The molding cycle consists of the descent from the top of the male mold on the female mold with approaching speed pneumatically adjustable.
- The molds (without electric resistances and equipped with self-centering system) are fixed on supports with heating resistances.
- The machine is equipped with a couple of height adjustable PLIERS to keep in position and to brake the flow of the material during the descent of the male mold to avoid the creation of creases (possible on some materials)
- All setting of temperature and times are adjustable with digital timers and thermoregulators.
- PLC controlled machine.
- The operation of changing the molds is easy and fast, is enough to connect the thermocouple plug to the socket on the machine.
- Presetable timer P90/TIM for automatic start-up and shut down of the unit on request.

### **TECHNICAL DATAS**

- Dimensions of the molds .....: 250 x 350 x H=150 mm
- Max molding temperature .....: 250°C.
- Installed power .....: 36 kW 400V 50 Hz 3-phase + Neutral + Ground.
- Compressed Air .....: 6 bar min (300 lt/hour).
- Time to change a size .....: 3 min

### **PRODUCTIVITY**

- Movement time of the mold (down + up) ..: 4 sec
- Molding time .....: from 60 to 180 sec depending on the material
- Loading/unloading time .....: 12 sec
- Production .....: up to 300 cups/hour (for a molding time of 2 min)