



A.M.P PISANI S.r.l. Via Ungaretti 6/8 27024 CILAVEGNA (PV) ITALY
Phone +39 0381 96128 Fax +39 0381 969100
www.amppisani.com email: info@amppisani.com



P88/4E

MOLDING MACHINE FOR FOAM BRA CUPS WITH FOUR MOLDS

MOLDING MACHINE FOR FOAM BRA CUPS WITH FOUR TWO MOLDS P88/4E

The machine P88/4E is a flexible unit with four DOUBLE molds and pliers specifically developed to mold bra cups in FOAM and it can produce No.8 cups per cycle.

TECHNICAL FEATURES

- The machine consists of four molding heads where it is possible to put one male mold in upper position and one female countermold (fixed) on the lower table. The molds are double (two cups on each mold) and the max dimensions are 350 x 250 x H=150 mm (can be increased to 390 x 290 x H=150 mm if female mold is equipped with pliers).
- The operator positions the rectangular pieces of foam on the loading/unloading stations then he starts the molding cycle.
- The molding cycle consists of the descent from the top of the male mold on the female mold with approaching speed pneumatically adjustable.
- The molds (without electric resistances and equipped with self-centering system) are fixed on supports with heating resistances.
- The machine is equipped with a couple of height adjustable PLIERS to keep in position and to brake the flow of the material during the descent of the male mold to avoid the creation of creases (possible on some materials)
- All setting of temperature and times are adjustable with digital timers and thermoregulators.
- PLC controlled machine.
- The operation of changing the molds is easy and fast, is enough to connect the thermocouple plug to the socket on the machine.
- Presettable timer P90/TIM for automatic start-up and shut down of the unit on request.

TECHNICAL DATAS

- Dimensions of the molds : 250 x 350 x H=150 mm
- Max molding temperature : 250°C.
- Installed power : 24 kW 400V 50 Hz 3-phase + Neutral + Ground.
- Compressed Air..... : 6 bar min (300 lt/hour).
- Time to change a size : 3 min

PRODUCTIVITY

- Movement time of the mold (down + up) .. : 4 sec
- Molding time : from 60 to 180 sec depending on the material
- Loading/unloading time : 10 sec
- Production : up to 200 cups/hour (for a molding time of 2 min)